

Technical drawing of a spherical lamp fixture. The main view shows a sphere with a diameter of $\phi 254$ and a height of $\langle 413 \rangle$. The mounting bracket has an outer diameter of $\phi 90$ and a height of 25. The mounting plate has a diameter of 66.7. The mounting plate has a $\phi 10 \times 5 \times 18$ mounting hole, a 5×10 mounting hole, and a $\phi 20$ power hole. The mounting plate is labeled 4, the mounting bracket is labeled 5, the mounting plate is labeled 3, the mounting bracket is labeled 2, and the mounting plate is labeled 1. The mounting plate is labeled 6 and the mounting bracket is labeled 7. The mounting plate is labeled 66.7, the mounting bracket is labeled $\phi 90$, the mounting plate is labeled $\phi 10 \times 5 \times 18$ 取付用ダマ穴, the mounting bracket is labeled 5×10 取付用穴, the mounting plate is labeled $\phi 20$ 電源穴, the mounting plate is labeled 器具外:110mm, the mounting bracket is labeled 25, the mounting plate is labeled $\phi 254$, and the mounting bracket is labeled $\langle 413 \rangle$.

別表

カラー	
-02	フ
-38	エ

気特性及び調光仕様

①

カラー	仕上色
-02	ブラック塗装仕上
-38	ゴールドメッキ仕上

指定LEDタイプ(別売)	定格電圧 (V)	定格周波数 (Hz)	定格入力電流 (A)	定格消費電力 (W)	定格入力容量 (VA)	調光	適合調光器	接続台数
LDA12L-G/100W/2 (ME99866-91)	AC100	50/60	0.20	12.0	20	不可	—	—
LDA8L-G-K/D/50W (ME99965-91)			0.15	8.2	15	可 (0~100%)	東芝製 WDG9012	単独取付時:16台 連接取付時:12台

7	取付ナット	真鍮	2	別表参照	本体OP01712、グローブOP01739 でお届けします。 ・LEDの光色には色ムがあります。 ご了承ください。	尺寸	1 / 4	品番	ML30175		
6	ワッシャー	鋼板	1	別表参照		重量	1.9 kg	電球	LED電球 E26 (別)		
5	アーム	鋼管	1	別表参照		検印	望月	印		印	島 箭
4	取付板	亜鉛鋼板	1	脱脂		特記事項					
3	カバー	鋼板	1	別表参照							
2	ソケット	磁器	1	E26							
1	グローブ	ガラス	1	乳白	作成日	2024.03.13		 maxRAY A Harmony of Light and Space			
部番	部品名	材質	数	備 考							

maxRAY
A Harmony of Light and Space